

Glancetron GT15plus

LCD monitor with integrated touch screen

- High-End 38.1 cm (15") LCD monitor for demanding applications
- Integrated touch screen with 5-wire resistive touch technology
- Extremely elegant design and especially robust construction
- Dual: touch screen interface with RS232/USB and AC/DC voltage supply
- Maximum resolution: 1,024 x 768 pixels



Specifications

General	Model	GT-15 plus
	Colour	Dark Grey
	Dimensions	321.9 x 364 x 206.08 mm (H x W x D)
	Net Weight / Shipping Weight	5.0 kg / 7.9 kg
	Power Supply	AC Input 90 ~ 264 V / DC 12 V
	Power Consumption	Operating: 25W (typ.) / Sleep: 4W / Off: 2W
Display	Mounting Option	Stand / 75 x 75 mm VESA Mount
	LCD Size / Type	15 Inch TFT Active Matrix Panel
	Active Area	304 x 228 mm (H x V)
	Pixel Pitch	0.297 x 0.297 mm (H x V)
	Panel Resolution	1,024 x 768 Pixels
	Display Mode	VGA 720 x 400 (70Hz)
	Display Colour	16.2 Million Colours
	Contrast	500:1
	Brightness	Without Touch 250 nits / SAW 230 nits / Capacitive 212 nits / Resistive 200 nits
	Response Time	Tr: 2 ms / Tf: 6 ms
Environment	Viewing Angle	Horizontal: 70° ~ -70° / Vertical: 65° ~ -60°
	Video Input Format	RGB Analog 0.7 Peak to Peak
	Video Sync Format	Separated H&V Sync. / Composite Sync. / Sync-on Green
	Video Input Frequency	Horizontal: 31Khz ~ 60.2 kHz / Vertical: 56 Hz ~ 76 Hz
	Video Signal Input	D.sub 15 pin Female (Analog)
	Temperature - Operating	0°C ~ +40°C
	Temperature - Storage	-20°C ~ +60°C
	Control Key	Power On/Off, Select, Down, Up, Menu
	Audio	1W Speaker / 2 Channels



Your Dealer